

A2007

7-channel, 200Wx7 smart power amplifier

Our 7-channel home theater amplifier in the Acurus A2000 series is the A2007. The A2007 is an all-in-one amplification solution for a high-performance, modern, HD home theater system. With THX Ultra2 certified specs and full integration with home automation systems, the A2007 delivers an uncompromising audio experience for home cinema.

An innovative Ethernet control and status port is now standard on all Acurus products. This smart feature enhances performance, setup and everyday use well beyond the basic 12-Volt trigger found in competitive products. Smart capabilities like this in all new Acurus products help ensure the best performance possible.

Applications

- Residential home theater
- Multipurpose home theater/2-channel systems
- Corporate media rooms
- Professional multichannel mastering studios

Solutions

- Detailed, neutral sound, ideal for music or movies
- Cool-running in rack or shelf placements
- Integrates multiple ways with automation systems
- Installation and setup simplified with web app
- US-made helps ensure quality and reliability
- Solid American engineering and construction for long-term reliability
- 5 year warranty

Features

- High-current output stage
- Fully discrete class AB analog audio circuitry
- Ethernet, RS-232, 12V trigger
- Temperature monitoring via web
- Rack-mount chassis designed for optimum cooling
- Mobile device controllable
- Remote monitor-ready



A2007



7-channel, 200Wx7 smart power amplifier

Optional accessories

- Rack ear kit (ARM-2)

Included

- User guide
- 14 AWG power cord
- Warranty card

Supporting documentation

- Ethernet and RS-232 control protocol
- 2-D CAD files
- Service guide
- International safety reports



Specifications

Electrical

Power output	200W (8Ω), 300W (4Ω), any 5 channels driven
THD	< 0.03% (200W, 8Ω), < 0.05% (300W, 4Ω)
Current capability	>18A (2.2Ω)
Frequency response	20 – 20kHz ±0.1dB
Tim/dim distortion	<0.003%
SNR	106dB (A-wt.)
Damping factor	500, 8Ω @ 50Hz
Input sensitivity	1W: 100mV, 200W: 1.42V
Input impedance	20kΩ
Power consumption	23W (idle), 1200W (max), <1W (standby)

Control

Ethernet/RS-232	Status and control of standby/on, channel configuration
12V	Standby/on control

Audio Inputs/Outputs

Audio in	Gold-plated RCA (unbalanced) x 7
Loudspeaker out	Gold-plated 60A 5-way binding posts x 7

Physical

Product dimensions	8.5" (21.6cm) x 17" (43.2cm) x 15.0" (38.1cm)
Rack height	5 RU
Product weight	52.2 lbs. (23.7kg)
Finish	Black satin anodized, laser-etched logo, white rear panel
Carton dimensions	16" (40.6cm) x 22" (55.9cm) x 20" (50.8cm)

